



safewaze.com | (P) 800-230-0319 | (F) 704-262-9051
 225 Wilshire Ave SW, Concord, NC 28025

TECHNICAL DATA SHEET

**** Item pictured - Part # 019-5040**



6' Web Personal SRL Series (Single Leg)

Features and Benefits The Latitude 6' Single Web Self Retracting Lifeline is a compact, lightweight unit designed for ease-of-use and all-day comfort. Featuring enhanced mobility, direct connection to all harnesses, and quick locking to arrest falls within inches, this SRL is an ideal solution for low heights

Length of Web 6 ft (1.83 m)

Weight of Unit *(See Page 2 for configuration options and weights)*

Materials Durable nylon housing
 .78 in (20 mm) Ultrahigh Molecular Weight Webbing
 Forged steel or Aluminum snap hook
 Forged Steel or Aluminum rebar hook
 Forged Steel or Aluminum carabiner

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength
 3,600 lbs (1632 kg) Gate Rated

Maximum Arresting Force <1,800 lbs (816.47 kg)

Maximum Arrest Distance Class A up to 24 in (60.96 cm) if used above Dorsal D-ring
 Class B up to 54 in (137.16 cm) if used up to a maximum of 5 ft below Dorsal D-ring

Maximum Working Load ANSI 130-310 lbs (58.97-140.61 kg)
 OSHA up to 420 lbs (190.51 kg)

Webbing Tensile Strength 4,200 lbs (1905.09 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32



safewaze.com | (P) 800-230-0319 | (F) 704-262-9051
 225 Wilshire Ave SW, Concord, NC 28025

6' Web Personal SRL Series Single Leg Configuration Options

SINGLE		Web Connection				Housing Connection			Weight in lbs. including carabiner			
Length in Feet	Material	3/4" Steel Snaphook	1.75" Aluminum Snaphook	1.75" Steel Rebar Hook	1.75" Aluminum Rebar Hook	Housing	No Carabiner	Steel Carabiner	Aluminum Carabiner			
019-5040	6	WEB	X					PLASTIC	X		2.36	
019-5041	6	WEB		X				PLASTIC	X		2	
019-5042	6	WEB				X		PLASTIC	X		3.35	
019-5043	6	WEB					X	PLASTIC	X		2.85	
019-5044	6	WEB	X					PLASTIC		X	2.91	
019-5045	6	WEB		X				PLASTIC		X	2.55	
019-5046	6	WEB				X		PLASTIC		X	3.9	
019-5047	6	WEB					X	PLASTIC		X	3.4	
019-5048	6	WEB	X					PLASTIC			X	2.69
019-5049	6	WEB		X				PLASTIC			X	2.33
019-5050	6	WEB				X		PLASTIC			X	3.68
019-5051	6	WEB					X	PLASTIC			X	3.18